# SAFETY DATA SHEET

Date Printed:

Supersedes Date: Sep 20, 2018

Jan 23, 2019

# SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: EA214-W

Product Name: RTV SILICONE WHITE

Revision Date: Jan 23, 2019

Version: 3.0

Manufacturer's Name:

Ecoline Industrial Supply Inc.

Address: PO Box 4236 Chatsworth CA 91313-4236

Emergency Phone: 1-800-424-9300 Information Phone Number: (800)425-8070

Fax:

Product/Recommended Uses: RTV Silicone Gasket Maker - Acetoxy

# **SECTION 2) HAZARDS IDENTIFICATION**

#### Classification

Eye Irritation - Category 2A

Gases Under Pressure Liquefied Gas

Skin Irritation - Category 2

### **Pictograms**





# Signal Word

Warning

# **Hazardous Statements - Physical**

H280 - Contains gas under pressure; may explode if heated

# **Hazardous Statements - Health**

H319 - Causes serious eye irritation

H315 - Causes skin irritation

### **Precautionary Statements - General**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

### **Precautionary Statements - Prevention**

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves and eye protection.

### **Precautionary Statements - Response**

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

#### **Precautionary Statements - Storage**

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

#### **Precautionary Statements - Disposal**

No precautionary statement available.

# **SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS**

| CAS          | Chemical Name                 | % By Weight |
|--------------|-------------------------------|-------------|
| 0070131-67-8 | METHYL SILOXANE LINEAR/CYCLIC | 52% - 82%   |
| 0007631-86-9 | SILICA, AMORPHOUS             | 5% - 12%    |
| 0064742-46-7 | MINERAL SEAL OIL              | 1% - 4%     |
| 0004253-34-3 | METHYLTRIACETOXYSILANE        | 1% - 4%     |
| 0017689-77-9 | ETHYLTRIACETOXYSILANE         | 1% - 4%     |
| 0000075-37-6 | DIFLUOROETHANE                | 1% - 2%     |

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

# **SECTION 4) FIRST-AID MEASURES**

#### Inhalation

No ill effects expected.

If exposed/feel unwell/concerned: Get medical attention.

# **Eye Contact**

Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

#### **Skin Contact**

Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

### Ingestion

Ingestion is not a likely route of exposure. Get medical attention if you feel unwell.

### **SECTION 5) FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Use extinguishing media suitable for surrounding fire.

# **Unsuitable Extinguishing Media**

None known.

#### Specific Hazards in Case of Fire

Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce silicon oxides; carbon oxides. Exposure of containers to heat and flames can cause them to rupture often with violent force.

### **Fire-Fighting Procedures**

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

### **Special Protective Actions**

Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

### **SECTION 6) ACCIDENTAL RELEASE MEASURES**

### **Emergency Procedure**

Ventilate the area. Wear appropriate protective clothing and equipment.

#### **Recommended Equipment**

Wear appropriate protective equipment (see Section 8).

Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

#### **Personal Precautions**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### **Environmental Precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

# **SECTION 7) HANDLING AND STORAGE**

#### General

Avoid contact with eyes and skin. Avoid breathing vapors or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

Do not puncture or incinerate (burn) cans. Do not spray in eyes. Do not take internally.

#### **Ventilation Requirements**

Use in a well-ventilated place.

### **Storage Room Requirements**

Store in a cool, dry, well-ventilated area, away from strong oxidizers and other incompatible materials. Do not store in direct sunlight or above 120°F.

# **SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION**

### **Eye Protection**

Safety glasses with side shields should be used if indicated. Eye wash and safety showers in the workplace are recommended.

#### **Skin Protection**

Use solvent-resistant protective gloves for prolonged or repeated contact.

### **Respiratory Protection**

In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

### Appropriate Engineering Controls

Ventilation should be sufficient to prevent inhalation of any vapors.

| Chemical Name     | OSHA<br>TWA<br>(ppm) | OSHA<br>TWA<br>(mg/m3)        | OSHA<br>STEL<br>(ppm) | OSHA<br>STEL<br>(mg/m3) | OSHA<br>Tables (Z1,<br>Z2, Z3) | OSHA<br>Carcinogen | OSHA<br>Skin<br>designation | NIOSH<br>TWA<br>(ppm) | NIOSH<br>TWA<br>(mg/m3) | NIOSH<br>STEL<br>(ppm) | NIOSH<br>STEL<br>(mg/m3) | NIOSH<br>Carcinogen |
|-------------------|----------------------|-------------------------------|-----------------------|-------------------------|--------------------------------|--------------------|-----------------------------|-----------------------|-------------------------|------------------------|--------------------------|---------------------|
| DIFLUOROETHANE    |                      | 2.5                           |                       |                         | 1                              |                    |                             |                       |                         |                        |                          |                     |
| MINERAL SEAL OIL  | 500                  | 2000                          |                       |                         | 1                              |                    |                             |                       |                         |                        |                          |                     |
| SILICA, AMORPHOUS | 20 (b)               | 80 mg/m3<br>percent<br>SiO2+2 |                       |                         | 1,3                            |                    |                             |                       | 6                       |                        |                          |                     |

| Chemical Name     | ACGIH<br>TWA<br>(ppm) | ACGIH<br>TWA<br>(mg/m3) | ACGIH<br>STEL<br>(ppm) | ACGIH<br>STEL<br>(mg/m3) |
|-------------------|-----------------------|-------------------------|------------------------|--------------------------|
| DIFLUOROETHANE    |                       | 2.5                     |                        |                          |
| MINERAL SEAL OIL  |                       |                         |                        |                          |
| SILICA, AMORPHOUS |                       |                         |                        |                          |

# **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

# **Physical and Chemical Properties**

 Density
 1.81942 lb/gal

 Density VOC
 0.25160 lb/gal

 % VOC
 3.07800%

Appearance Thick liquid under pressure (Viscous paste)

Odor Threshold N.A.

Odor Description Acetic Acid Odor

pH N.A. Water Solubility N.A.

Flammability Flash point at or above 200°F/93°C

Flash Point Symbol N.A.

Flash Point >100 °C(>212°F) Closed Cup (Liquid component)

Viscosity N.A. Lower Explosion Level N.A. Upper Explosion Level N.A. Vapor Density N.A. Melting Point N.A. Freezing Point N.A. Low Boiling Point N.A. High Boiling Point N.A. Decomposition Pt N.A. Auto Ignition Temp N.A. **Evaporation Rate** N.A.

# **SECTION 10) STABILITY AND REACTIVITY**

# Stability

The product is stable under normal storage conditions.

#### **Conditions to Avoid**

Keep away from heat, sparks, extreme temperature, flame, other sources of ignition and incompatible materials.

#### **Incompatible Materials**

Strong acids, strong bases, strong oxidizing agents.

### **Hazardous Reactions/Polymerization**

None known.

#### **Hazardous Decomposition Products**

Burning may produce silicon oxides; carbon oxides.

# **SECTION 11) TOXICOLOGICAL INFORMATION**

### Skin Corrosion/Irritation

Causes skin irritation

#### Classification of the substance or mixture

There is no toxicological data available for this product.

# Serious Eye Damage/Irritation

Causes serious eye irritation

### Carcinogenicity

No data available

### **Germ Cell Mutagenicity**

No data available

### **Reproductive Toxicity**

No data available

# Respiratory/Skin Sensitization

No data available

### **Specific Target Organ Toxicity - Single Exposure**

No data available

# **Specific Target Organ Toxicity - Repeated Exposure**

No data available

### **Aspiration Hazard**

No data available

### **Acute Toxicity**

No data available

# **SECTION 12) ECOLOGICAL INFORMATION**

# **Toxicity**

No data available

#### Classification of the substance or mixture

There is no ecological data available for this product.

### **Persistence and Degradability**

No data available.

#### **Bio-Accumulative Potential**

No data available.

#### Mobility in Soil

No data available.

#### Other Adverse Effects

No data available.

# **SECTION 13) DISPOSAL CONSIDERATIONS**

### **Waste Disposal**

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

### **SECTION 14) TRANSPORT INFORMATION**

#### **U.S. DOT Information**

UN number: UN1950

Proper shipping name: Aerosols, non-flammable

Hazard class: 2.2

Packaging group: No Data Available

Hazardous substance (RQ): No Data Available Toxic-Inhalation Hazard: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision: (each not exceeding 1 L capacity) (LTD QTY)

# **IMDG Information**

UN number: UN1950

Proper shipping name: Aerosols, non-flammable

Hazard class: 2.2

Packaging group: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision: (each not exceeding 1 L capacity) (LTD QTY)

# **IATA Information**

UN number: UN1950 Hazard class: 2.2

Packaging group: No Data Available

Proper shipping name: Aerosols, non-flammable

Note / Special Provision: (each not exceeding 1 L capacity) (LTD QTY)

# **SECTION 15) REGULATORY INFORMATION**


| CAS          | Chemical Name                    | % By Weight | Regulation List                    |
|--------------|----------------------------------|-------------|------------------------------------|
| 0070131-67-8 | METHYL SILOXANE<br>LINEAR/CYCLIC | 52% - 92%   | SARA312,TSCA                       |
| 0007631-86-9 | SILICA, AMORPHOUS                | 5% - 12%    | SARA312,TSCA,OSHA                  |
| 0064742-46-7 | MINERAL SEAL OIL                 | 1% - 4%     | SARA312,TSCA,OSHA                  |
| 0004253-34-3 | METHYLTRIACETOXYSIL<br>ANE       | 1% - 4%     | SARA312,TSCA                       |
| 0017689-77-9 | ETHYLTRIACETOXYSILA<br>NE        | 1% - 4%     | SARA312,TSCA                       |
| 0000075-37-6 | DIFLUOROETHANE                   | 1% - 2%     | SARA312,VOC_exempt,TSCA,ACGIH,OSHA |

# **SECTION 16) OTHER INFORMATION**

### Glossary

\* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



### (\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

### **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.