Safety Data Sheet

Printing date 01/06/2023 Revised On 01/06/2023

1 Identification of the substance and manufacturer

Trade name: **RUST EXTERMINATOR**

Product code: EQ1650

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Ecoline Industrial Supply, Inc.

PO Box 4236 Chatsworth, CA

91313 (800) 425-8070

Emergency telephone number: 1-800-424-9300 Ecoline Industrial Supply, Inc. PO Box 4236 Chatsworth, CA

91313 (800) 425-8070

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**

Precautionary statements









Danger

Signal word Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description This product is a mixture of the substances listed below with nonhazardous additions

escription.	This product is a mixture of the substances listed below with hornazardous additions.		
Dangerous components:			
Acetone		15-25%	
propane		15-25%	
		10-15%	
Talc		10-15%	
n-butane		5-10%	
diacetone alcohol		1-5%	
propylene glycol		1-5%	
		1-5%	
methyl isobutyl ketone		1-5%	
Methyl Propyl Ketone		1-5%	
PM acetate		1-5%	
	components: Acetone propane tert-butyl acetate Talc n-butane diacetone alcohol propylene glycol VM&P Naphtha methyl isobutyl ketone Methyl Propyl Ketone	components: Acetone propane tert-butyl acetate Talc n-butane diacetone alcohol propylene glycol VM&P Naphtha methyl isobutyl ketone Methyl Propyl Ketone	

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact:

Rinse out mouth and then drink plenty of water. After swallowing: Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

(Contd. of page 1)

(Contd. on page 3)

Safety Data Sheet

Printing date 01/06/2023 Revised On 01/06/2023

Trade name: RUST EXTERMINATOR

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

Dizziness

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

No further relevant information available.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

REL (USA)

TLV (USA)

108-65-6 PM acetate

Long-term value: 530 mg/m³, 150 ppm

Short-term value: 150 ppm

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

<u> </u>	controls/personal protection
	s with limit values that require monitoring at the workplace:
67-64-1 Ace	
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm
REL (USA)	Long-term value: 590 mg/m³, 250 ppm
TLV (USA)	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI
74-98-6 proj	pane
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)
540-88-5 ter	t-butyl acetate
PEL (USA)	Long-term value: 950 mg/m³, 200 ppm
REL (USA)	Long-term value: 950 mg/m³, 200 ppm
TLV (USA)	Short-term value: 150 ppm Long-term value: 50 ppm
106-97-8 n-k	outane Control of the
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm
TLV (USA)	Short-term value: 1000 ppm (EX)
123-42-2 dia	cetone alcohol
PEL (USA)	Long-term value: 240 mg/m³, 50 ppm
REL (USA)	Long-term value: 240 mg/m³, 50 ppm
TLV (USA)	Long-term value: 50 ppm
57-55-6 proj	pylene glycol
WEEL (USA	Long-term value: 10 mg/m³
108-10-1 me	thyl isobutyl ketone
PEL (USA)	Long-term value: 410 mg/m³, 100 ppm
REL (USA)	Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm
TLV (USA)	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3
107-87-9 Me	thyl Propyl Ketone
PEL (USA)	Long-term value: 700 mg/m³, 200 ppm

WEEL (USA) Long-term value: 50 ppm

(Contd. of page 2)

Printing date 01/06/2023 Revised On 01/06/2023

Trade name: RUST EXTERMINATOR

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: Do not eat or drink while working.

A respirator is generally not necessary

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Aromatic Odor: Odor threshold: Not determined. Not determined. pH-value: Melting point/Melting range Undetermined. -44 °C (-47.2 °F) Boiling point: -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % 10.9 Vol % Vapor pressure: Not determined. Vapor density Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: No decomposition if used according to specifications.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 v	LD/LC50 values that are relevant for classification:				
123-42-2	123-42-2 diacetone alcohol				
Oral	LD50	4,000 mg/kg (rat)			
Dermal	LD50	13,630 mg/kg (rab)			
108-10-1 r	108-10-1 methyl isobutyl ketone				
Oral	LD50	2,100 mg/kg (rat)			
Dermal	LD50	16,000 mg/kg (rab)			
Inhalative	LC50/4 h	11 mg/l (ATE)			
		8.3-16.6 mg/l (rat)			
108-65-6 F	108-65-6 PM acetate				
Oral	LD50	8,500 mg/kg (rat)			
Inhalative	LC50/4 h	35.7 mg/l (rat)			

(Contd. on page 4)

(Contd. of page 3)

Printing date 01/06/2023 Revised On 01/06/2023

Trade name: RUST EXTERMINATOR

Information on toxicological effects: No data available. Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Persistence and degradability: Hazardous for water, do not empty into drains.

The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

Bioaccumulative potential: No further relevant information available. No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT LIN1950

Aerosols, flammable DOT ADR 1950 Aerosols

Transport hazard class(es):

Class Marine pollutant: 2.1 Gases No

Special precautions for user:

Warning: Gases

EMS Number:

F-D,S-Ŭ

Packaging Group: UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

1333-86-4 Carbon black

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64-1 Acetone

Т 108-10-1 methyl isobutyl ketone Τ

16 Other information

Contact: Regulatory Affairs