

# SAFETY DATA SHEET



Date Prepared : 11/25/2013

MSDS No : METAL EPOXY-GHS - RESIN

Date-Revised : 12/13/2016

Revision No : 8

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT DESCRIPTION:** POWER BOND 5  
PART #ET2521

### MANUFACTURER

Ecoline Industrial Supply, Inc  
PO Box 4236  
Chatsworth, CA 91313-4236  
Emergency Contact: Chemtrec  
Phone: 800-424-9300

## 2. HAZARDS IDENTIFICATION

### GHS CLASSIFICATIONS

#### Health:

Skin Irritation, Category 2  
Eye Irritation, Category 2A  
Skin Sensitization, Category 1  
Reproductive Toxicity, Category 2

#### Environmental:

Aquatic Hazard (Long-Term), Category 2

### GHS LABEL ELEMENTS

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



Exclamation  
mark



Health  
hazard

**SIGNAL WORD:** WARNING

### HAZARD STATEMENTS

H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H361: Suspected of damaging fertility or the unborn child.  
H411: Toxic to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENT(S)

#### Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264: Wash skin and hands thoroughly after handling.

# SAFETY DATA SHEET



Date Prepared : 11/25/2013  
 MSDS No : METAL EPOXY-GHS - RESIN  
 Date-Revised : 12/13/2016  
 Revision No : 8

P272: Contaminated work clothing should not be allowed out of the workplace.  
 P273: Avoid release to the environment.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P362: Take off contaminated clothing.  
 P363: Wash contaminated clothing before reuse.  
 P391: Collect spillage.

## Response:

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P302+352: IF ON SKIN: Wash with plenty of soap and water.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P332+P313: If skin irritation occurs: Get medical advice/attention.  
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313: If eye irritation persists: Get medical advice/attention.

## Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

## Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Epoxy resin (Bisphenol A)	80 - 100	25068-38-6
Bisphenol F epoxy resin	1 - 10	9003-36-5

## 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

**SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists.

**INGESTION:** If swallowed, do not induce vomiting. Keep individual calm. Get medical attention and show container label.

**INHALATION:** Remove to fresh air. Get medical attention if breathing is difficult.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Causes eye irritation.

**SKIN:** Irritating to skin. May cause allergic skin reaction with prolonged contact.

**SKIN ABSORPTION:** None known.

**INGESTION:** May be irritating. Seek medical advice.

**INHALATION:** Prolonged or excessive inhalation may cause respiratory tract irritation.

**ACUTE EFFECTS:** Slightly irritating to eyes and respiratory tracts.

**CHRONIC EFFECTS:** Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

## 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

# SAFETY DATA SHEET



Date Prepared : 11/25/2013

MSDS No : METAL EPOXY-GHS - RESIN

Date-Revised : 12/13/2016

Revision No : 8

**HAZARDOUS COMBUSTION PRODUCTS:** Decomposition and products may be toxic. Thermal breakdown of the product during fired or very high heat conditions may product the following: carbon monoxide, carbon dioxide, and isobutene.

**EXPLOSION HAZARDS:** None known.

**FIRE FIGHTING PROCEDURES:** Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

**FIRE FIGHTING EQUIPMENT:** As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

**FIRE EXPLOSION:** None known.

**SENSITIVE TO STATIC DISCHARGE:** None known.

**SENSITIVITY TO IMPACT:** None Known.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion products may include: carbon monoxide, carbon dioxide, hydrogen gas and oxides of nitrogen.

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Absorb liquid and place in sealed container for disposal

**LARGE SPILL:** Contain spill with dike to prevent entry into sewers. Absorb liquid and place in sealed container for disposal.

### ENVIRONMENTAL PRECAUTIONS

**WATER SPILL:** Avoid runoff into storm sewers and ditches which lead to waterways.

**LAND SPILL:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

**AIR SPILL:** None known.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

**HANDLING:** Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes, and clothing. Keep Container closed when not in use.

**STORAGE:** Store in a cool place in original container and protect from sunlight. Protect from freezing.

**STORAGE TEMPERATURE:** Ambient room temperature (70F/21C).

**LOADING TEMPERATURE:** Not Established

**LOADING/UNLOADING VISCOSITY:** Not Established

**STORAGE PRESSURE:** Not Established

**ELECTROSTATIC ACCUMULATION HAZARD:** None known.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Not Established

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

**SKIN:** Wear rubber gloves to avoid prolonged skin contact.

# SAFETY DATA SHEET



Date Prepared : 11/25/2013  
MSDS No : METAL EPOXY-GHS - RESIN  
Date-Revised : 12/13/2016  
Revision No : 8

**RESPIRATORY:** In case of insufficient ventilation, wear suitable respiratory equipment.

**PROTECTIVE CLOTHING:** Wear rubber gloves and apron.

**WORK HYGIENIC PRACTICES:** Avoid contact with skin and eyes. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Viscous liquid.

**ODOR:** Moderate odor.

**ODOR THRESHOLD:** No data available

**APPEARANCE:** Light yellow viscous liquid.

**pH:** No data available

**PERCENT VOLATILE:** No data available

**FLASHPOINT AND METHOD:** > 93°C (200°F) CC - Closed Cup

**AUTOIGNITION TEMPERATURE:** No data available

**VAPOR PRESSURE:** No data available

**VAPOR DENSITY:** No data available

**BOILING POINT:** No data available

**FREEZING POINT:** No data available

**MELTING POINT:** No data available

**POUR POINT:** No data available

**THERMAL DECOMPOSITION:** No data available

**SOLUBILITY IN WATER:** Insoluble

**EVAPORATION RATE:** No data available

**DENSITY:** No data available

**SPECIFIC GRAVITY:** 1.16

**VISCOSITY #1:** 20000 to 40000 Centipoise

**MOLECULAR WEIGHT:** No data available

**(VOC):** 0 g/L

## 10. STABILITY AND REACTIVITY

**HAZARDOUS POLYMERIZATION:** No

**STABILITY:** Stable

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition or burning may release oxides of carbon and nitrogen.

**INCOMPATIBLE MATERIALS:** Strong oxidizing agents, acids and bases.

## 11. TOXICOLOGICAL INFORMATION

**ACUTE TOXICITY**

# SAFETY DATA SHEET



Date Prepared : 11/25/2013

MSDS No : METAL EPOXY-GHS - RESIN

Date-Revised : 12/13/2016

Revision No : 8

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)
Epoxy resin (Bisphenol A)	> 2000 mg/kg (rat)	> 2000 mg/kg (rat)
Bisphenol F epoxy resin	> 5000 mg/kg (rat)	> 2000 mg/kg (rat)

**SKIN CORROSION/IRRITATION:** None known.**SERIOUS EYE DAMAGE/IRRITATION:** Prolonged or repeated skin contact may cause irritation and/or dermatitis.**RESPIRATORY OR SKIN SENSITISATION:** May cause sensitization.**GERM CELL MUTAGENICITY:** None known.**CARCINOGENICITY****IARC:** Not listed.**NTP:** Not listed.**OSHA:** Not listed.**REPRODUCTIVE TOXICITY:** None known.**STOT-SINGLE EXPOSURE:** None known.**STOT-REPEATED EXPOSURE:** None known.

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** Do not flush to sewer.**ECOTOXICOLOGICAL INFORMATION:** No data available**BIOACCUMULATION/ACCUMULATION:** No data available

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**PRODUCT DISPOSAL:** Avoid runoff into storm sewers and ditches which lead to waterways.**EMPTY CONTAINER:** Dispose of following all Local Authority requirements for disposal.

## 14. TRANSPORT INFORMATION

**DOT (DEPARTMENT OF TRANSPORTATION)****PROPER SHIPPING NAME:** NOT REGULATED (IP VOL LESS THAN OR EQUAL TO 450.0 L)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A EPOXY RESIN), 9, III (IP VOL GREATER THAN 450.0 L)

**AIR (ICAO/IATA)**

# SAFETY DATA SHEET



Date Prepared : 11/25/2013  
 MSDS No : METAL EPOXY-GHS - RESIN  
 Date-Revised : 12/13/2016  
 Revision No : 8

**SHIPPING NAME:** ID8000, CONSUMER COMMODITY, 9 (IP VOL LESS THAN OR EQUAL TO 0.5 L); or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A EPOXY RESIN), 9, III (LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0 L)\*

## VESSEL (IMO/IMDG)

**SHIPPING NAME:** UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A EPOXY RESIN), 9, III (LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0 L)\*

**COMMENTS:** \* This product may be shipped as EXCEPTED QUANTITIES OF CLASS 9, UN3082 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN OR EQUAL TO 1.0 L)

The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

## 15. REGULATORY INFORMATION

### UNITED STATES

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**FIRE:** No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** No

**TITLE III NOTES:** To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Epoxy resin (Bisphenol A)	25068-38-6
Bisphenol F epoxy resin	9003-36-5

**CALIFORNIA PROPOSITION 65: WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. (Bisphenol A Resin CAS 25068-38-6)

Chemical Name	Wt. %	Listed
Epoxy resin (Bisphenol A)	80 - 100	Female Reproductive

## 16. OTHER INFORMATION

**APPROVED BY:** Pacer Technology Regulatory Department

**PREPARED BY:** Pacer Technology Regulatory Department **Date-Revised:** 12/13/2016

**REVISION SUMMARY:** This MSDS replaces the 11/14/2016 MSDS. Revised: **Section 2:** . **Section 9:** VISCOSITY. **Section 12:** ECOTOXICOLOGICAL INFORMATION, BIOACCUMULATION/ACCUMULATION. **Section 14:** AIR (ICAO/IATA) - SHIPPING NAME COMMENTS, DOT (DEPARTMENT OF TRANSPORTATION) - PROPER SHIPPING NAME VESSEL (IMO/IMDG) - SHIPPING NAME. **Section 15:** CALIFORNIA PROPOSITION 65.

# SAFETY DATA SHEET



Date Prepared : 11/25/2013

MSDS No : METAL EPOXY-GHS - RESIN


Date-Revised : 12/13/2016

Revision No : 8

## HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY	<input type="checkbox"/>	1
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	

## NFPA CODES



## MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Ecoline Industrial Supply, Inc. does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.