## **TECHNICAL DATA SHEET**

## POWER FOAM CA™

**HEAVY DUTY FOAMING DEGREASER** 

PART NUMBER(S):

EA570-CA AEROSOL CAN NET WT 18-16 OZ Power Foam CA is a unique aerosol foam which enables simple and easy degreasing of engines, tools, parts, workbenches, vent covers, machinery, coils, industrial equipment, concrete and more. It sprays as an engulfing, heavy-duty foam that clings to surfaces and provides extended degreasing contact time. Power Foam CA contains a potent blend of water-soluble, grease-dissolving agents and detergents that provide powerful degreasing action. It features a self-indicating foam which quickly breaks down grease and grime and becomes discolored, indicating when grease and grime are ready to be flushed away. Power Foam CA deodorizes as it degreases, leaving the area with a fresh citrus aroma.

**WHO:** Road maintenance crews, grounds departments, HVAC technicians, building engineers, facility maintenance personnel, public transportation, mechanics, public works, municipalities, gas and oil companies, power plants, fleet departments, manufacturing plants, construction and maintenance

**WHERE:** Automotive engines, public vehicles, machinery, tools, lawn equipment, construction equipment, road equipment, driveways and parking lots, industrial equipment, air conditioning coils, exhaust vents

WHAT: Grease, grime, dirt, soils, odors

## **FEATURES AND BENEFITS:**

- Powerful high-pressure spray
- Thick clinging foam
- Fast grease-dissolving action

**DIRECTIONS:** SHAKE WELL BEFORE USING. For best results, spray directly onto greasy surfaces. Look for self-indicating foam to break and become discolored. Agitate as needed and flush with water stream. For difficult to remove contaminants, allow foam to remain on surface for several minutes before agitating and flushing. Repeat application as needed. A stiff bristled brush may be useful for loosening stubborn deposits. CAUTION: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**ACTIVE INGREDIENTS:** Water (7732-18-5), Butane (106-97-8), Diethylene Glycol Monoethyl Ether (111-90-0), Distillates (Petroleum), Hydrotreated Light (64742-47-8), Isopropyl Alcohol (67-63-0), Polyethylene Glycol Nonylphenol Ether (9016-45-9), Propane (74-98-6) and Sodium Metasilicate Anhydrous (6834-92-0).

**HMIS RATINGS:** Health: 2; Flammability: 2; Physical Hazard: 0; Personal Protection: X.



TOLL FREE: 800.425.8070

ECOLINE INDUSTRIAL SUPPLY, INC GOECOLINE.COM