

TECHNICAL DATA SHEET

RUBBERIZED COATING

FLEXIBLE AND WATER-TIGHT FILM

PART NUMBER(S):

EA947

AEROSOL CAN NET WT 20-16 OZ

Rubberized Coating provides a super-thick, black, durable, and flexible rubberized film. It's designed to seal and acoustically reduce unwanted sound and vibration. Rubberized Coating protects metal parts against the harmful effects of water, salt, sand, and road chemicals. It provides a great solution for sealing minor cracks and pinholes. It stays pliable in winter cold and will not sag, melt, or drip in the summer heat. Its formula resists cracking, peeling, and abrasion. Rubberized Coating works on a variety of surfaces: metal, wood, roofing materials, tin, concrete. It's easy to apply without a need for clean-up.

WHO: Roofing contractors, maintenance crews, building engineers, plumbers, auto and diesel repair shops, garages, taxi companies, construction companies, machine shops, equipment manufacturers, air conditioning maintenance, truck fleet maintenance, and public transportation maintenance operations

WHERE: Overlapping seams, gravel stops, chimney and skylight flashing, vents and pipe flashing, mobile home and camper roof seams, A/C drip pans, gutters, below-grade foundations, automobiles

WHAT: Minor leaks, cracks, voids, vibration reduction, waterproof sealing, corrosion protection

FEATURES AND BENEFITS:

- Protects against corrosion
- Reduces unwanted sound and vibration
- Seals minor cracks and voids

DIRECTIONS: Shake can vigorously. Clean surface of dirt and rust. Hold can 12 inches from surface. Spray a thin even coat building up desired thickness. Remove overspray with cloth dampened with kerosene. To prevent clogging of tip, turn can upside down and depress tip for 2 seconds. Wipe tip clean. Caution: Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

ACTIVE INGREDIENTS: Acetone (67-64-1), Propane (74-98-6), Toluene (108-88-3), Calcium Carbonate (1317-65-3), Xylene (1330-20-7), Carbon Black (1333-86-4), Crystalline Silica (14808-60-7) and Naphtha (petroleum), Hydrotreated light (64742-49-0).

HMIS RATINGS: Health: 1; Flammability: 4; Physical Hazard: 0; Personal Protection: X.



TOLL FREE:
800.425.8070

ECOLINE INDUSTRIAL SUPPLY, INC
GOECOLINE.COM