## **TECHNICAL DATA SHEET**

## **RUST EXTERMINATOR**

NON-CHLORINATED RUST NEUTRALIZER

PART NUMBER(S): EA165

AEROSOL CAN NET WT 16-11 OZ

Rust Exterminator chemically neutralizes rust and leaves a tough, long term, rust preventative coating. Seals, protects and prolongs the life of ferrous metal. Rusted area turns to a black protective finish. Upon curing, the protective barrier can be painted if desired. NOTE: Wearing chemical resistant gloves is recommended.

**WHO:** Painters, HVAC technicians, plumbers, building engineers, mechanics, welders, fleet departments, sheet metal shops, public works, municipalities, public transportation, power plants, gas and oil companies.

**WHERE:** Rusted metals, condensate pans, railings, rusted pipes, industrial equipment, buses, car suspensions, railroad equipment, marine equipment, aircraft parts, oil rigs, snow plow equipment, shovels, storage tanks.

**WHAT:** Corrosion, rust.

## **FEATURES AND BENEFITS:**

- Stops corrosion
- Seals ferrous metals and protects from rust
- Paintable after curing

**DIRECTIONS:** 1. For best results, workpiece and can should be at room temperature (above 65°F.). 2. Surfaces must be clean, dry and free of grease, dirt and oil. Remove loose rust and paint with coarse sandpaper or a wire brush. 3. Before using, shake can until ball rattles freely for at least one minute. Holding the can 8 to 10 inches from the surface, spray a thin, even coating onto the rusted metal. Avoid over application, sagging and dripping. A second application is advised only after allowing for complete drying of initial application. Final application will dry to a black finish. May be painted after curing for approximately 6 hours. CAUTION: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**ACTIVE INGREDIENTS:** Acetone (67-64-1), Butane (106-97-8), Isopropyl Alcohol (67-63-0), Propane (74-98-6), Propylene Glycol Methyl Ether (107-98-2), Tannic Acid (1401-55-4) and Toluene (108-88-3).

**HMIS RATINGS:** Health, 3\*; Flammability, 4; Physical Hazard, 0; Personal Protection, X. \*=Chronic



TOLL FREE: 800.425.8070

ECOLINE INDUSTRIAL SUPPLY, INC GOECOLINE.COM