



TECHNICAL DATA SHEET

PRODUCT NAME: ANTI SLIP EPOXY COATING "GOOD GRIP"-CLEAR

PRODUCT NUMBER: EA610-CL

PRODUCT DESCRIPTION, FEATURES AND BENEFITS:

Hard, texturized, epoxy resin coating that quickly cures to a slip resistant rough grit surface. Aids in the reduction of slip and fall accidents. Unique aerosol contains special synthetic grit with no sharp edges. Available in several colors. One application lasts for months depending on traffic.

APPLICATIONS:

For use in areas where water may accumulate: kitchen floors, steps, ladders, railings, and industrial plants.

PROPERTIES:

Odor:	Aromatic
Boiling Point:	-44°C
Flash Point:	-19°C
Auto Igniting:	Product is not self –igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120°F. In use, may form flammable/explosive vapor-air mixture.
Lower Explosion Limit:	1.7 Vol%
Upper Explosion Limit:	10.9 Vol%
Vapor Pressure:	40 psi, 2750 hPa
Density @ 20°C:	076 g/cm3
Specific Gravity:	Between 0.77 and 085 (water equals 1.00)
VOC Content:	519.6 g/l 4.34 lb/gl
VOC Content (less exempt solvents):	42.7%
MIR Value:	1.47
Solids Content:	18.8%

ACTIVE INGREDIENTS (CAS NUMBER):

(67-64-1) Acetone 31.91%, (74-98-6) propane 13.87%, (106-97-8) n-butane 8.15%, (1330-20-7) xylene (mix) 7.08%, (108-65-6) PM acetate 5.92%, (108-10-1) methyl isobutyl ketone 5.17%, (1317-65-3) Calcium Carbonate 3.94%, (112926-00-8) Silicone Dioxide Amorphous Synthetic 1.99%, (100-41-4) ethyl benzene 1.77%.

SAFETY:

Extremely flammable. Harmful by inhalation. Irritating to eyes. Do not breathe gas/fumes/vapor/spray. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas. Keep out of the reach of children.

HMIS RATINGS:

Health: 1; Flammability: 4; Reactivity: 3.

ECOLINE INDUSTRIAL SUPPLY, INC.
MANUFACTURED BY SEYMOUR
800-425-8070