

## TECHNICAL DATA SHEET

# PRIME BLACK

FOR USE ON BARE METAL AND BARE  
WOOD SURFACES

**PART NUMBER(S):**

EA131-BL 16-12 OZ (340 GRAMS)

**A fast drying spray primer that provides maximum rust protection and adhesion for a finishing top coat. Can be used with lacquer, enamel, and acrylic paints. Provides excellent resistance to heat and corrosion. VOC compliant. For best results, sand lightly with fine sandpaper or steel wool prior to applying finish coat. For use on bare metal and bare wood surfaces.**

**WHO:** Vehicle maintenance, painters, plumbers, building engineers, power plants, sheet metal shops, municipalities, air conditioning maintenance, public transportation, fire departments, machine shops, restaurant owners, marine maintenance, gas and oil companies, agricultural maintenance, military, road crews, aircraft maintenance.

**WHERE:** Radiators, steam pipes, fire hydrants, exhausts, mufflers, parking meters, chain & wire fences, boilers, engines, lockers, heat exchangers, ovens, storage & mixing tanks, chemical processing & production equipment, oil rigs, restaurant equipment, other metal, wood, and ceramic surfaces.

**WHAT:** Corrosion resistance and protection against alkalis, acids, harsh chemicals, weather, sunlight, oil, water.

**FEATURES AND BENEFITS:**

- PROVIDES MAXIMUM RUST PROTECTION
- FAST DRY, SAG FREE SPRAY
- EFFECTIVE AGAINST RUST & CHEMICALS
- INDOOR/OUTDOOR DURABILITY

**DIRECTIONS:**

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50F and 90F (10C and 32C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other object into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

**ACTIVE INGREDIENTS:** Acetone (67-64-1), Propane (74-98-6), Isobutyl Acetate 110-19-0), N-Butane (106-97-8), VM&P Naphtha (64742-89-8), Isopropyl Alcohol (67-63-0), N-Butyl Acetate (123-86-4) Talc (14807-96-6), Mineral Spirits (64742-48-7), PM Acetate (108-65-6), Xylene (1330-20-7), Butyl Acetate (123-86-64).

**HMIS RATINGS:** Health: 1, Flammability: 4; Reactivity: 3; Personal Protection: 0



**TOLL FREE:**  
**800.425.8070**

**ECOLINE INDUSTRIAL SUPPLY, INC**  
**GOECOLINE.COM**