

## TECHNICAL DATA SHEET

# NO MESS ANTI-SEIZE™ COPPER

HIGH TEMPERATURE  
ZERO MESS ANTI-SEIZE AND  
LUBRICANT

**PART NUMBER(S):**

EA839-C

PRESSURIZED CAN 6 FL OZ

No Mess Anti-Seize™ Copper is a premium anti-seize lubricant containing no lead or copper for maximum resistance to the most corrosive and extreme temperature environments. It has a non-melting synthetic carrier which depolymerizes and dissipates at temperatures exceeding 400°F without leaving a carbon residue. No Mess Anti-Seize™ Copper will deposit film of nickel and graphite to plate and protect metal surfaces to temperatures up to 1800°F (982°C). Its water resistant formula effectively protects against rust and corrosion, and prevents seizing and galling. No Mess Anti-Seize™ Copper utilizes innovative design in a pressurized can with shoe-polish applicator to prevent the product from drying, ensure mess free application and extend its shelf-life up to 5 years.

**WHO:** Machine shops, electricians, plumbers, HVAC technicians, road maintenance crews, roofers, building engineers, facility maintenance personnel, public transportation, public works, municipalities, gas and oil companies, power plants, assembly and manufacturing plants, construction and maintenance, water and sewage treatment plants, aircraft, metal working, steel mills and foundries, marinas, shipyards, chemical plants, textile mills, farms and irrigation, automotive, truck and fleet maintenance, pulp and paper mills, fire departments

**WHERE:** Nuts and bolts, spark plugs, threaded fittings, gaskets, flanges, valves, bushings, unions, key-ways, any type of metal parts moving in high temperature

**WHAT:** Rust, corrosion, seizing, galling, chemicals, extreme environments

**FEATURES AND BENEFITS:**

- Waterproof, chemical and corrosion resistant
- High temperature up to 2100°F (1095°C)
- Prevents seizing and galling
- 

**DIRECTIONS:** All surfaces should be cleaned before application. Depress nozzle to apply to threads or other surfaces which require protection. Interchangeable applicator tips allow you to apply a bead line of lubricant or brush it on with application pad.

**ACTIVE INGREDIENTS (CAS NO.):** Copper (7440-50-8), Synthetic Grease (NJTSRN 1210-01), Distillates (Petroleum) Hydrotreated Heavy Naphthenic (64742-52-5), Rust Inhibitor (mixture).

**HMIS RATINGS:** Health: 1; Flammability: 0; Reactivity: 0; Personal Protection: A.



**TOLL FREE:**  
**800.425.8070**

**ECOLINE INDUSTRIAL SUPPLY, INC**  
**GOECOLINE.COM**