

## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

### Section 1: Company and Product Identification

Ecoline Industrial Supply, Inc.  
9520 Owensmouth Ave., Unit 3  
Chatsworth, CA 91311  
(800) 425-8070

24-Hour Emergency Telephone: (800) 255-3924

Product ID: **EA860**

Product Name: PAINT STRIPPER, Aerosol, 12x18 oz

Intended Use: PAINT STRIPPER

### Section 2: Hazard(s) Identification

**Product Signal Word: DANGER**

**Physical Hazard Classification:** Flammable Aerosols, Category 1  
Extremely flammable aerosol.

#### Physical Hazard Precautionary Statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Protect from sunlight.

Do not expose to temperatures exceeding 50 °C/122°F.



#### Health Hazard Classification(s):

Acute Toxicity - Dermal - Level 4

Acute Toxicity - Inhalation - Level 4

Skin Corrosion/Irritation -Level 2

Eye Damage/Irritation -Level 1

Carcinogenicity - Level 1

Toxic to Reproduction - Level 1

Specific Target Organ Toxicity (Single Exposure) -

Specific Target Organ Toxicity (Single Exposure) -



## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

### Health Hazard Statements:

Harmful in contact with skin.

Causes skin irritation.

Causes serious eye damage.

Harmful if inhaled.

May cause respiratory irritation.

May cause cancer.

May damage fertility or the unborn child.

May cause damage to organs.



### First-Aid Statement(s):

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

Immediately call a POISON CENTER/doctor/physician.

Call a POISON CENTER/doctor/physician if you feel unwell.

See section 12 if specific treatment is applicable.

See Section 12 if specific treatment is applicable.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing.

Wash contaminated clothing before reuse.

### Handling and Storage Statement(s):

Use personal protective equipment as required.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

### Exposure Control / Personal Protection Statement(s):

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash hands and exposed areas thoroughly after handling.

## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

### Disposal Statement(s):

Dispose of contents/container in accordance with local regulations.

### Section 3: Product Composition

	CAS#	% Range		PEL	TLV
HYDROCARBON PROPELLANT	68476-86-8	10%	30%	NO DATA	NO DATA
METHYL ALCOHOL *	67-56-1	10%	20%	200 ppm	200 ppm
DICHLOROMETHANE *	75-09-2	40%	60%	TWA 25 ppm	ACGIH 50 ppm
AROMATIC HYDROCARBON *	108-88-3	1%	5%	TWA OF 100 ppm(375	TWA OF 50 ppm (147 mg/m3)
TALL OIL	61790-12-3	1%	5%	NOT ESTABLISHED	NOT ESTABLISHED
AMMONIUM HYDROXIDE	7664-41-7	1%	5%	50 PPM	35 PPM

Specific chemical identity and exact percentages are withheld as Trade Secret.

### Section 4: First-Aid Measures

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

Immediately call a POISON CENTER/doctor/physician.

Call a POISON CENTER/doctor/physician if you feel unwell.

See section 12 if specific treatment is applicable.

See Section 12 if specific treatment is applicable.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing.

Wash contaminated clothing before reuse.

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury,



## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

possibly minimal toxicity.

### FIRST AID

**EYE CONTACT:** Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**SKIN CONTACT:** Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

**INHALATION:** Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention

**INGESTION:** If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

### PRECAUTIONS

**SPECIAL PRECAUTIONS:** Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

**PERSONAL PROTECTION:** For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

**VENTILATION:** The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

## Section 5: Fire-Fighting Measures

**FIRE AND EXPLOSION HAZARDS:** This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

**EXTINGUISHING MEDIA:** Dry Chemical. CO<sub>2</sub>. Halogenated Extinguishing Agent. Stop Gas Flow.

**SPECIAL FIREFIGHTING PROCEDURES:** Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

**FIRE FIGHTING:** Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

## Section 6: Accidental Release Measures

### STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:

Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

**WASTE DISPOSAL METHOD:** Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

## Section 7: Handling and Storage

Use personal protective equipment as required.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.



## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

**VENTILATION REQUIREMENT:** Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

**RESPIRATORY PROTECTION:** Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

**EYES:** Face shield and goggles or chemical goggles should be worn.

**GLOVES:** Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

**OTHER CLOTHING EQUIPMENT:** Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

**RESPIRATORY PROTECTION:** In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

### Section 8: Exposure Control / Personal Protection

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash hands and exposed areas thoroughly after handling.

Do no eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

**VENTILATION REQUIREMENT:** Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

**RESPIRATORY PROTECTION:** Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

**EYES:** Face shield and goggles or chemical goggles should be worn.

**GLOVES:** Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

**OTHER CLOTHING EQUIPMENT:** Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

**RESPIRATORY PROTECTION:** In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

### Section 9: Product Properties

Flash Point (CCP): LEVEL 3 AEROSOL, PROPELLENT: -136°F



## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

Boiling Point for Product: N/D  
Vapor Pressure for Product: N/D  
Vapor Density for Product: N/D  
Specific Gravity: 1.13 - 1.16  
V.O.C.: 35%  
Water Solubility: NEGLIGIBLE  
Appearance: SEMI VISCOUS LIQUID  
PH:

### Section 10: Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

### Section 11: Toxicological Information

METHYL ALCOHOL \* 67-56-1

**Routes of Entry:** Absorbed through skin. Eye contact. Inhalation. Ingestion.

**Toxicity to Animals:**

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 5628 mg/kg [Rat]. Acute dermal toxicity (LD50): 15800 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 64000 4 hours [Rat].

**Chronic Effects on Humans:**

MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Classified POSSIBLE for human. Causes damage to the following organs: eyes. May cause damage to the following organs: blood, kidneys, liver, brain, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS), optic nerve.

**Other Toxic Effects on Humans:**

Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

DICHLOROMETHANE \* 75-09-2

**Acute oral toxicity:** LD50 Rat: 1600 mg/kg;

**Acute inhalation toxicity:** LC50 Rat: 5200 mg/m3;

Investigated as a tumorigen, mutagen, reproductive effector.

AFFECTS CENTRAL NERVOUS SYSTEM, LIVER, CARDIOVASCULAR SYSTEM, AND BLOOD. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. SUSPECT CANCER HAZARD.

AROMATIC HYDROCARBON \* 108-88-3

**Acute oral toxicity:** LD50 Rat: 2,600 - 7,500 mg/kg

**Acute inhalation toxicity:** LC50 Rat: 8,000 ppm, 4 h

**Acute dermal toxicity:** LD50 Rabbit: 12,124 mg/kg

TALL OIL 61790-12-3

Due to viscosity may serve as an aspiration hazard if liquid enters the lungs. Do not induce vomiting if swallowed.

## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

AMMONIUM HYDROXIDE 7664-41-7

**Routes of Entry:** Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

**Toxicity to Animals:** Acute oral toxicity (LD50): 350 mg/kg [Rat].

**Chronic Effects on Humans:**

MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. [Ammonium hydroxide]. May cause damage to the following organs: mucous membranes, skin, eyes.

**Other Toxic Effects on Humans:**

Very hazardous in case of skin contact (corrosive, irritant, permeator), of ingestion, . Hazardous in case of eye contact (corrosive), of inhalation (lung corrosive).

## Section 12: Ecological Information

METHYL ALCOHOL \* 67-56-1

**Ecotoxicity:** Ecotoxicity in water (LC50): 29400 mg/l 96 hours [Fathead Minnow].

**Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

**Toxicity of the Products of Biodegradation:** The products of degradation are less toxic than the product itself.

**Special Remarks on the Products of Biodegradation:**

Methanol in water is rapidly biodegraded and volatilized. Aquatic hydrolysis, oxidation, photolysis, adsorption to sediment, and bioconcentration are not significant fate processes. The half-life of methanol in surfact water ranges from 24 hrs. to 168 hrs. Based on its vapor pressure, methanol exists almost entirely in the vapor phase in the ambient atmosphere. It is degraded by reaction with photochemically produced hydroxyl radicals and has an estimated half-life of 17.8 days. Methanol is physically removed from air by rain due to its solubility. Methanol can react with NO<sub>2</sub> in polluted to form methyl nitrate. The half-life of methanol in air ranges from 71 hrs. (3 days) to 713 hrs. (29.7 days) based on photooxidation half-life in air.

DICHLOROMETHANE \* 75-09-2

**Environmental Fate:**

When released into the soil, this material may leach into groundwater. When released into the soil, this material is expected to quickly evaporate. When released into water, this material may biodegrade to a moderate extent. When released to water, this material is expected to quickly evaporate. This material has a log octanol-water partition coefficient of less than 3.0. This material is not expected to significantly bioaccumulate. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life of greater than 30 days. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition.

**Environmental Toxicity:**

The LC50/96-hour values for fish are over 100 mg/l. This material is not expected to be toxic to aquatic life.

AROMATIC HYDROCARBON \* 108-88-3

**Bioaccumulation**

Species: Ide, silver or golden orfe (*Leuciscus idus*)

Exposure time: 3 d

Dose: 0.05 mg/l

Bioconcentration factor (BCF): 94

Method: Not reported

**Ecotoxicity effects**

**Toxicity to fish**

96 h LC 50 Rainbow trout, donaldson trout (*Oncorhynchus mykiss*): 5.80 mg/l

Method: Renewal, Mortality

96 h LC 50 Fathead minnow (*Pimephalespromelas*): 12.60 mg/l

Method: Static Mortality

**Toxicity to daphnia and other aquatic invertebrates.**

48 h EC 50 Water flea (*Daphnia magna*): 6.00 mg/l

Method: Static, Intoxication

AMMONIUM HYDROXIDE 7664-41-7

**Ecotoxicity:**

Ecotoxicity in water (LC50): 0.1 ppm 24 hours [Rainbow trout]. 8.2mg/l 96 hours [Fathead minnow]. 0.1 ppm 48 hours



## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

[Bluegill].

**BOD5 and COD:** Not available.

**Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

**Toxicity of the Products of Biodegradation:** The products of degradation are less toxic than the product itself.

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "\*". Additional ecological information is Not Determined.

### Section 13: Disposal Information

Dispose of contents/container in accordance with local regulations.

**WASTE DISPOSAL METHOD:** Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

### Section 14: Transportation Information

DOT Proper Shipping Name: UN1950

Aerosols, flammable, (each not exceeding 1L capacity) 2.1

### Section 15: Regulatory Information

	CAS#	PEL	TLV
HYDROCARBON PROPELLANT	68476-86-8	NO DATA	NO DATA
METHYL ALCOHOL *	67-56-1	200 ppm	200 ppm
DICHLOROMETHANE *	75-09-2	TWA 25 ppm	ACGIH 50 ppm
AROMATIC HYDROCARBON *	108-88-3	TWA OF 100 ppm(375	TWA OF 50 ppm (147 mg/m3)
TALL OIL	61790-12-3	NOT ESTABLISHED	NOT ESTABLISHED
AMMONIUM HYDROXIDE	7664-41-7	50 PPM	35 PPM

State of California SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986.

**WARNING:** IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM.

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "\*".

### Section 16: Other Information

Consumer Product Safety Act Certification.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.





## SAFETY DATA SHEET

SDS PREP DATE: 12/29/2016

SDS REVISION DATE: 12/29/2016

**Product ID: EA860**

**24-Hour Emergency Telephone: (800) 255-3924**

---

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.